



AS-R series

Electric Reefers

Perfect for Stationary and Transportable Refrigerated Spaces

TRANSPORTABLE UNIT

FRESH OR FROZEN TEMPS

WEATHER RESISTANT

SINGLE BLOCK CONSTRUCTION



COLD IN MOTION

transport refrigeration system
Transblock®



AS-R/AS-E rotary compressor

Special units for mobile cold rooms, refrigerated containers and auxiliary storage trailers up to 53 feet in length

- High reliability during transport
- Suitable for outdoor use
- Remote Automatic control
- Automatic Stop/Start
- Automatic Temperature Control through Microprocessor
- HCFC Free R404 freon lowers environmental Impact
- Reduced Maintenance
- High Voltage Fans
- High Capacity, Compact and Extremely Versatile
- Only "STORAGE SPECIFIC ALL ELECTRIC UNIT" available on the market
- Highest BTU output available in the Industry
- Multi-temperature version available
- Combined Low and Med temp units (PAS)



Zanotti launches the Industries First and Only Original Equipment all Electric Storage Unit uniquely engineered, specifically from the Bench Up, as the Most efficient, Environmentally Responsible, and Maintenance Friendly solution for the growing needs of Auxillary refrigeration space. The AS Series is Engineered and designed to take advantage of Zanotti's rich history and experience in Commercial/Industrial refrigeration and transform it into the Mobile Warehouse and Storage environment. No belts, No pulleys, in fact very few moving parts, ensures longevity, consistency, less maintenance and thoroughly exceeded expectations.

Zanotti has created the AS series in an aesthetically appealing yet rugged "Epoxide" Powder Coated exterior casing that will weather extremely well and provides easy access

REFRIGERATED VOLUME

*Tc	32 °F	
*Ta	+86 °F	+104 °F
MAS	315 ft ³ to 6,880 ft ³	245 ft ³ to 5,890 ft ³
BAS	105 ft ³ to 6,250 ft ³	105 ft ³ to 4,908 ft ³

COOLING CAPACITY

*MAS	3,680 BTU/h - 40,500 BTU/h
*BAS	2,450 BTU/h - 29,870 BTU/h

* Referring cold room thickness: 100 mm

TECHNICAL DATA

Models	MAS		BAS	
Working temperature	+59 to 32 °F	+50 to 32 °F	-5 to -13 °F	
Gas	R407C	R404A	R404A	
Defrost	Hot Gas		Hot Gas	
Weight	116 - 537 Lb		127 - 600 Lb	
COMPRESSOR				
Compressor type	Hermetic	Scroll	Hermetic	Scroll
Nominal power	0.5 - 7.25 Hp		1 - 10 Hp	
EVAPORATOR				
Air flow	350 - 4.000 cfm		300 - 4.000 cfm	
Air throw	13 to 53 ft		13 to 53 ft	

Multitemperature version available (+41 to - 23 °F / -5 to - 13 °F)



LEGEND			
Tc	cold room temperature	Ta	ambient temperature

Contact Zanotti USA:

www.zanottitransblock.com

1-856-393-7230

©Copyright Zanotti Spa All right reserved. Technical data, descriptions, and pictures are to be considered provisional and not binding. Zanotti Spa reserves the right to bring such a literature,